

#### TIDES

shown on front: 28130 12x24 Sand Castle

Florida Tile's Tides is a stylized interpretation of vein cut limestone known as "Georgette". It is a stunning play of tone-ontone colors that creates a contemporary aesthetic. Using Florida Tile's HDP-High Definition Porcelain® technology we are able to create a unique tonal blend within the veining to add interest and depth to each graphic.

This glazed porcelain floor and wall tile is available in pressed 12x24 and a rectified 3.75x12 in three color options: Sea Salt, Marine Fog, and Sand Castle. Also featured in each color is a

unique patterned 25-piece mosaic that rotates each chip 90 degrees creating a wonderful checkerboard pattern. A 3x24 bullnose completes the line.

Tides is appropriate for most applications in both residential and commercial settings. It is made in the USA in our Green Squared® certified Advanced Manufacturing Center in Lawrenceburg, KY. It includes pre-consumer recycled content and is GREENGUARD® and Porcelain Tile certified.

shown: 28115 12x24 Marine Fog & 28130/M12 Sand Castle Mosaic



# SEA SALT



**28110 3.75x12** Sea Salt



**28110 12x24** Sea Salt



**28110/M12** Sea Salt 25pc Mosaic

## MARINE FOG



**28115 3.75x12** Marine Fog



**28115 12x24** Marine Fog



**28115/M12**Marine Fog 25pc Mosaic

## SAND CASTLE



**28130 3.75x12** Sand Castle



**28130 12x24** Sand Castle



28130/M12 Sand Castle 25pc Mosaic



above: 28110 12x24 Sea Salt

Technical Specifications	Results <sup>1</sup>
ANSI® A326.3 <sup>2</sup>	Interior, Wet (IW)  Mosaics Interior, Wet Plus (IW+)
Surface Hardness	7 Mohs
Break Strength	≥ 510 lbf. avg.
Water Absorption	≤ 0.5%³
Intended Use <sup>4</sup>	Residential & Light Commercial

<sup>&</sup>lt;sup>1</sup> Values are offered in good faith as being accurate and typical of normal production. Due to the natural variation of raw materials and manufacturing processes, the values of the purchased product for any particular installation may vary.

<sup>&</sup>lt;sup>4</sup> Please visit www.floridatile.com/intended-use for further details.

Field Tile Nominal Size (in) <sup>1</sup>	Metric (cm)	Pcs./Sq Ft <sup>2</sup>	Thickness <sup>3,4</sup>	Edge
3.75x12	9.5x30	3.27	9mm	Rectified
12x24	30x60	.5	9mm	Pressed

<sup>&</sup>lt;sup>1</sup>These values may vary from lot to lot.

<sup>&</sup>lt;sup>4</sup> In order to enhance manufacturing efficiencies this product has been modified to a 9mm thickness. During implementation of this modification, some 10mm products will remain available. Please confirm the thickness of your product at time of order.

Trim	Shape	Sku	Nominal Size (in) <sup>1</sup>	Metric (cm)
Bullnose		P43N9	3x24	7.5x60


<sup>&</sup>lt;sup>1</sup>These values may vary from lot to lot.

#### **Typical Uses**

Tides glazed porcelain floor and wall tile is appropriate for most residential and commercial wall, countertop, backsplash, and floor applications.

Notice: Not all flooring products are suitable for wet areas, specialized applications, or commercial use. Please refer to the American National Standard Specifications for Ceramic Tile (ANSI® A137.1) for ceramic, stone, and glass installation for specific usage and installation information.

This Florida Tile product will contribute to USGBC LEED® points and the ANSI® approved NAHB® Green Building Points.



Color, texture, and finish variations may occur due to the nature of the product.

Country of origin and other product features and characteristics are subject to change due to manufacturing efficiencies and other factors. See retailer or product packaging to verify country of origin and other product characteristics.

Color reproductions in this printed piece may vary from actual tile colors. Final selection should be made from actual tile samples.













<sup>&</sup>lt;sup>2</sup> For more information, visit floridatile.com/productuseclassifications.

<sup>&</sup>lt;sup>3</sup> Average production value.

<sup>&</sup>lt;sup>2</sup>These values are based on actual sizes including the grout joint.

<sup>&</sup>lt;sup>3</sup> May not apply to textured surfaces or tiles with uneven back patterns such as mesh mounted mosaics.